

- INT 213
- INT 230
- INT 236
- INT 237
- INT 245
- INT 288
- INT 420
- INT 450
- INT 460
- INT 468
- INT 470
- INT 480
- INT 490
- INT 510
- INT 520
- INT 530
- INT 540
- INT 549
- INT 560

**Description :** decorative films enhance clear glass with a wide range of designs and patterns. Add privacy and style to office partitions, ground level windows, doors and many other applications.

**For :** facades, office partitions, computer rooms, hospitals, floor level rooms, schools, workshops, decoration of devantures, etc...

**Application method :** internal surface with soapy water.

**Glass maintenance :** the film may be cleaned with soapy water, 30 days after the application. Any abrasive products that could scratch the film, are not recommended. Do not apply any stickers, or any other type of adhesives on the film.

**Durability :** 12 to 15 years for vertical application in Central Europe.

**Storage :** 2 years from the delivery date. This film has to be kept away from excessive humidity. It also has to be stored away from direct sunlight at a temperature under 38°C.

**Important factors :** the glass surface used must be entirely dirt free and any grease or other filth must be removed prior to installation. Gas may be given off from certain polycarbonate surfaces which are too new or of mediocre quality. This may be unsightly but does not lessen the adhesive qualities of the film. Users are recommended to carry out a trial beforehand to avoid bubbling

Fire performance class

**M1**

Please make sure to match the correct specifications when applying your film. You may follow the glass compatibility guideline, especially concerning thermal stress.

Please note that Reflectiv does not guaranty the glass quality or the incorrect use of its films and claims the possibility of changing the production process or tints without previous notification.

Material	Polyester 36 microns
Adhesive	Acrylic polymer 13 gr/m <sup>2</sup>
Release liner	Siliconed polyester 23 microns
Application	Internal
INT 213	Stripes of 13 mm x 6 mm of clear
INT 230	Stripes of 3 cm and 3 mm
INT 236	Fine decreasing stripes
INT 237	Thick decreasing stripes
INT 245	Stripes of 45 mm x 10 mm of clear
INT 288	Wave height of 45 mm
INT 420	Frosted with two 2mm clear stripes
INT 450	Frosted squares of 45 x 45 mm
INT 460	Mini transparent squares
INT 468	Frosted squares with rounded angles
INT 470	Squares of 2 cm spaced of 5 cm
INT 480	Frosted rosettes of 50 x 50 cm
INT 490	Frosted crossed lines
INT 510	Frosted vertical curves
INT 520	Frosted broken glass
INT 530	Frosted trees
INT 540	Frosted circles and curves
INT 549	Frosted vertical stripes
INT 560	Frosted decreasing stripes
Thermal resistance	from -20°C to 80°C
Application temperature	Minimum 5°C
Dimensions	60'' x 8,34' 60'' x 33,34' 60'' x 100'